		Page: 1
<b>SAFETY DATA SHEET</b>		Revision Date: 05/19/2017
		Print Date: 5/17/2018
		SDS Number: R0172170
Valvoline™ Multi-Vehicle Multi-Purpose Red Grease ™ Trademark, Valvoline or its subsidiaries, registered in various countries VV615		Version: 1.3

29 CFR 1910.1200 (OSHA HazCom 2012)

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

**Product identifier**

Trade name : Valvoline™ Multi-Vehicle Multi-Purpose Red Grease  
™ Trademark, Valvoline or its subsidiaries, registered in various countries

<b>Details of the supplier of the safety data sheet</b> Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL	<b>Emergency telephone number</b> 1-800-VALVOLINE (1-800-825-8654)  <b>Regulatory Information Number</b> 1-800-TEAMVAL  <b>Product Information</b> 1-800-TEAMVAL
---	---

**SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification**

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

**GHS label elements**

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous components**

Chemical name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	Asp. Tox. 1; H304	74.9999
ASPHALT	8052-42-4	This material is not considered hazardous under the OSHA Hazard	24.9999



**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 5/17/2018

SDS Number: R0172170

Version: 1.3

Valvoline™ Multi-Vehicle Multi-Purpose Red Grease  
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries  
 VV615

		Communication Standard (HazCom 2012).	
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT	64742-52-5	This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	9.9999

**SECTION 4. FIRST AID MEASURES**

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.  
If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Remove contact lenses.  
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through



**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 5/17/2018

SDS Number: R0172170

Version: 1.3

Valvoline™ Multi-Vehicle Multi-Purpose Red Grease  
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries  
 VV615

the skin may include:  
 stomach or intestinal upset (nausea, vomiting, diarrhea)  
 irritation (nose, throat, airways)

Notes to physician : No hazards which require special first aid measures.

**SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
 Water spray  
 Foam  
 Carbon dioxide (CO2)  
 Dry chemical

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide  
 Sulphur oxides  
 Hydrocarbons  
 Aldehydes  
 Ketones  
 Nitrogen oxides (NOx)

Specific extinguishing methods :  
 Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
 Keep in suitable, closed containers for disposal.

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 5/17/2018

SDS Number: R0172170

Version: 1.3

Valvoline™ Multi-Vehicle Multi-Purpose Red Grease  
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries  
 VV615

Other information : Comply with all applicable federal, state, and local regulations.

**SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.  
 For personal protection see section 8.

Materials to avoid : No materials to be especially mentioned.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ASPHALT	8052-42-4	TWA	0.5 mg/m3 Fume, inhalable fraction (benzene soluble aerosol)	ACGIH
		C	5 mg/m3 Fumes	NIOSH REL
		PEL	5 mg/m3 Fumes	CAL PEL
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT	64742-52-5	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL

**Hazardous components without workplace control parameters**

Components	CAS-No.
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 5/17/2018

SDS Number: R0172170

Version: 1.3

Valvoline™ Multi-Vehicle Multi-Purpose Red Grease  
™ Trademark, Valvoline or its subsidiaries, registered in various  
countries  
VV615

**Engineering measures** : General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

**Personal protective equipment**

Respiratory protection : No personal respiratory protective equipment normally required.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear as appropriate:  
Safety shoes  
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : General industrial hygiene practice.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : gel

Physical state : liquid

Colour : red

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : 640 °F / 338 °C

Flash point : 471 °F / 244 °C

Evaporation rate : No data available

Flammability (solid, gas) : No data available

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 5/17/2018

SDS Number: R0172170

Version: 1.3

Valvoline™ Multi-Vehicle Multi-Purpose Red Grease  
™ Trademark, Valvoline or its subsidiaries, registered in various  
countries  
VV615

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : < 0.01 mmHg (20 °C)

Relative vapour density : No data available

Relative density : 0.95 (15.6 °C)

Density : 0.90 g/cm<sup>3</sup> (20 °C)

Solubility(ies)

Water solubility : negligible

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : > 315 °C

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20.5 mm<sup>2</sup>/s (40 °C)

Oxidizing properties : No data available

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : None known.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 5/17/2018

SDS Number: R0172170

Version: 1.3

Valvoline™ Multi-Vehicle Multi-Purpose Red Grease  
™ Trademark, Valvoline or its subsidiaries, registered in various  
countries  
VV615

products

carbon dioxide and carbon monoxide  
Hydrocarbons  
Sulphur oxides

**SECTION 11. TOXICOLOGICAL INFORMATION**

Information on likely routes of exposure : Inhalation  
Skin contact  
Eye Contact  
Ingestion

**Acute toxicity**

Not classified based on available information.

**Product:**

Acute oral toxicity : Acute toxicity estimate (Rat): 3,019 mg/kg

Acute dermal toxicity : Acute toxicity estimate (Rabbit): 169,492 mg/kg

**Components:**

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): &gt; 5,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): &gt; 5,000 mg/kg

## ASPHALT:

Acute oral toxicity : LD50 (Rat): &gt; 5,000 mg/kg

Acute inhalation toxicity : Assessment: Not classified as acutely toxic by inhalation  
under GHS.  
Remarks: Information given is based on data obtained from  
similar substances.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Assessment: Not classified as acutely toxic by dermal  
absorption under GHS.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT:

Acute oral toxicity : LD50 (Rat): &gt; 5 g/kg

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: Not classified as acutely toxic by inhalation  
under GHS.

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 5/17/2018

SDS Number: R0172170

Version: 1.3

Valvoline™ Multi-Vehicle Multi-Purpose Red Grease  
™ Trademark, Valvoline or its subsidiaries, registered in various  
countries  
VV615

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Assessment: Not classified as acutely toxic by dermal  
absorption under GHS.  
Remarks: No mortality observed at this dose.

**Skin corrosion/irritation**

Not classified based on available information.

**Product:**

Result: No skin irritation

**Components:**

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Result: Slight, transient irritation

**ASPHALT:**

Species: Rabbit

Result: No skin irritation

Remarks: Information given is based on data obtained from similar substances.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT:

Species: Rabbit

Result: No skin irritation

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Result: No eye irritation

Remarks: Unlikely to cause eye irritation or injury.

**Components:**

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Result: Slight, transient irritation

**ASPHALT:**

Species: Rabbit

Remarks: May irritate eyes.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT:

Species: Rabbit

Result: Slight, transient irritation

**Respiratory or skin sensitisation**

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

**Components:****ASPHALT:**

Test Type: Buehler Test



**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 5/17/2018

SDS Number: R0172170

Version: 1.3

Valvoline™ Multi-Vehicle Multi-Purpose Red Grease  
™ Trademark, Valvoline or its subsidiaries, registered in various  
countries  
VV615

Species: Guinea pig  
Assessment: Does not cause skin sensitisation.

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT:**

Species: Guinea pig  
Assessment: Does not cause skin sensitisation.  
Method: OECD Test Guideline 406

Germ cell mutagenicity  
Not classified based on available information.

**Components:****ASPHALT:**

Genotoxicity in vitro : Result: Positive results were obtained in some in vitro tests.

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.

**Product:**

No aspiration toxicity classification

**Components:****DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:**

May be fatal if swallowed and enters airways.

**Further information****Product:**

Remarks: No data available

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Product:**

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

**Components:****ASPHALT:**

Toxicity to fish : Remarks: No toxicity at the limit of solubility  
QSAR

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 5/17/2018

SDS Number: R0172170

Version: 1.3

Valvoline™ Multi-Vehicle Multi-Purpose Red Grease  
 ™ Trademark, Valvoline or its subsidiaries, registered in various  
 countries  
 VV615

Toxicity to daphnia and other aquatic invertebrates : Remarks: No toxicity at the limit of solubility  
 QSAR

Toxicity to algae : Remarks: No toxicity at the limit of solubility  
 QSAR

Toxicity to fish (Chronic toxicity) : Remarks: No toxicity at the limit of solubility  
 QSAR

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT:**

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
 Exposure time: 96 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l  
 Exposure time: 48 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l  
 End point: Growth inhibition  
 Exposure time: 72 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l  
 Exposure time: 21 d  
 Test Type: semi-static test  
 Test substance: WAF  
 Method: OECD Test Guideline 211

**Persistence and degradability****ASPHALT:**

Biodegradability : Result: Not readily biodegradable.

**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHT:**

Biodegradability : Result: Inherently biodegradable.  
 Biodegradation: 31 %  
 Exposure time: 28 d  
 Method: OECD Test Guideline 301F

No data available

**Bioaccumulative potential**

No data available



**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 5/17/2018

SDS Number: R0172170

Version: 1.3

Valvoline™ Multi-Vehicle Multi-Purpose Red Grease  
™ Trademark, Valvoline or its subsidiaries, registered in various countries  
VV615

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**

Additional ecological information : No data available

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.

**SECTION 14. TRANSPORT INFORMATION**

**International transport regulations**

**REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

**U.S. DOT - ROAD**

Not dangerous goods

**CFR\_RAIL\_C**

Not dangerous goods

**U.S. DOT - INLAND WATERWAYS**

Not dangerous goods

**TDG\_ROAD\_C**

Not dangerous goods

**TDG\_RAIL\_C**

Not dangerous goods

**TDG\_INWT\_C**



**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 5/17/2018

SDS Number: R0172170

Version: 1.3

Valvoline™ Multi-Vehicle Multi-Purpose Red Grease  
™ Trademark, Valvoline or its subsidiaries, registered in various countries  
VV615

Not dangerous goods

**INTERNATIONAL MARITIME DANGEROUS GOODS**

Not dangerous goods

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

Not dangerous goods

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**

Not dangerous goods

**MX\_DG**

Not dangerous goods

**\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

**SECTION 15. REGULATORY INFORMATION**

**EPCRA - Emergency Planning and Community Right-to-Know Act  
CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : No SARA Hazards

**SARA 313** This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**California Prop 65** Proposition 65 warnings are not required for this product based on the results of a risk assessment.

**The components of this product are reported in the following inventories:**

TSCA : On TSCA Inventory

AICS : On the inventory, or in compliance with the inventory

**SAFETY DATA SHEET**

Revision Date: 05/19/2017

Print Date: 5/17/2018

SDS Number: R0172170

Version: 1.3

Valvoline™ Multi-Vehicle Multi-Purpose Red Grease  
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries  
 VV615

- DSL : All components of this product are on the Canadian DSL
- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory


**Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

**SECTION 16. OTHER INFORMATION**

**Further information**

Revision Date: 05/19/2017

<p><b>NFPA:</b></p>  <p style="text-align: center;">Special hazard.</p>	<p><b>HMIS III:</b></p> <table border="1" style="width: 100%;"> <tr> <td style="background-color: blue; color: white;"><b>HEALTH</b></td> <td style="text-align: center;"><b>0</b></td> </tr> <tr> <td style="background-color: red; color: white;"><b>FLAMMABILITY</b></td> <td style="text-align: center;"><b>1</b></td> </tr> <tr> <td style="background-color: yellow; color: black;"><b>PHYSICAL HAZARD</b></td> <td style="text-align: center;"><b>0</b></td> </tr> </table> <p>0 = not significant, 1 =Slight,                  2 = Moderate, 3 = High                  4 = Extreme, * = Chronic</p>	<b>HEALTH</b>	<b>0</b>	<b>FLAMMABILITY</b>	<b>1</b>	<b>PHYSICAL HAZARD</b>	<b>0</b>
<b>HEALTH</b>	<b>0</b>						
<b>FLAMMABILITY</b>	<b>1</b>						
<b>PHYSICAL HAZARD</b>	<b>0</b>						


**NFPA Flammable and Combustible Liquids Classification**

Combustible Liquid Class IIIB

**Full text of H-Statements**

H304 May be fatal if swallowed and enters airways.

Sources of key data used to compile the Safety Data Sheet  
 Valvoline internal data including own and sponsored test reports

	Page: 14
<b>SAFETY DATA SHEET</b>	Revision Date: 05/19/2017
	Print Date: 5/17/2018
	SDS Number: R0172170
Valvoline™ Multi-Vehicle Multi-Purpose Red Grease ™ Trademark, Valvoline or its subsidiaries, registered in various countries VV615	Version: 1.3

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.


The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists  
BEI : Biological Exposure Index  
CAS : Chemical Abstracts Service (Division of the American Chemical Society).  
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction  
FG : Food grade  
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.  
H-statement : Hazard Statement  
IATA : International Air Transport Association.  
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization  
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"  
IMDG : International Maritime Code for Dangerous Goods  
ISO : International Organization for Standardization  
logPow : octanol-water partition coefficient  
LCxx : Lethal Concentration, for xx percent of test population  
LDxx : Lethal Dose, for xx percent of test population.  
ICxx : Inhibitory Concentration for xx of a substance  
Ecxx : Effective Concentration of xx  
N.O.S.: Not Otherwise Specified  
OECD : Organization for Economic Co-operation and Development  
OEL : Occupational Exposure Limit  
P-Statement : Precautionary Statement  
PBT : Persistent , Bioaccumulative and Toxic  
PPE : Personal Protective Equipment  
STEL : Short-term exposure limit  
STOT : Specific Target Organ Toxicity  
TLV : Threshold Limit Value  
TWA : Time-weighted average  
vPvB : Very Persistent and Very Bioaccumulative  
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act  
DOT : Department of Transportation  
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act  
HMIRC : Hazardous Materials Information Review Commission  
HMIS : Hazardous Materials Identification System  
NFPA : National Fire Protection Association

	Page: 15
<b>SAFETY DATA SHEET</b>	Revision Date: 05/19/2017
	Print Date: 5/17/2018
	SDS Number: R0172170
Valvoline™ Multi-Vehicle Multi-Purpose Red Grease ™ Trademark, Valvoline or its subsidiaries, registered in various countries VV615	Version: 1.3

NIOSH : National Institute for Occupational Safety and Health  
OSHA : Occupational Safety and Health Administration  
PMRA : Health Canada Pest Management Regulatory Agency  
RTK : Right to Know  
WHMIS : Workplace Hazardous Materials Information System