



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

#### Sales, Service & Distribution Center

Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

#### Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

#### Sales and Tech Service Support

Phone: 1-800-733-4755

## PRODUCT DATA

# LUBRIPLATE WHEEL BEARING GREASE

## DESCRIPTION & APPLICATIONS

LUBRIPLATE Wheel Bearing Grease is a non-corrosive, extreme pressure, water resistant, shear stable lubricant designed for:

### All Grease Type Wheel Bearings

- ⇒ Pickups
- ⇒ Cruisers
- ⇒ Heavy Duty Trucks
- ⇒ Highway Truck Trailers
- ⇒ Boat, House & Recreational Trailers
- ⇒ Passenger Cars
- ⇒ Vans
- ⇒ Light & Medium Trucks
- ⇒ Off-Highway Equipment

## ADVANTAGES

LUBRIPLATE Wheel Bearing Grease has a high dropping point making it ideal for wheel bearings on vehicles having disc brakes. This lubricant also has a good cold operating temperature making it the “one” wheel bearing lubricant for all temperatures, except the extreme arctic regions.



## Typical Test Data

PROPERTY	TEST METHOD	TYPICAL RESULTS*
Thickener		Lithium 12-Hydroxy Stearate Complex
Penetration Range	ASTM D-217	265/295
NLGI No.		2
ASTM Dropping Point	ASTM D-566	550°F/288°C
Worked Penetration: 60 Strokes	ASTM D-217	270
1,000 Strokes	ASTM D-217	273
10,000 Strokes	ASTM D-217	282
100,000 Strokes	ASTM D-217	297
Fluid Viscosity: SUS @ 100°F	ASTM D-2161	1100
cSt @ 40°C	ASTM D-445	215
SUS @ 210°F	ASTM D-2161	92
cSt @ 100°C	ASTM D-445	18
Flash Point	ASTM D-92	500°F/260°C
Fire Point	ASTM D-92	545°F/285°C
Specific Gravity	ASTM D-4052	0.96
Timken E.P. Test: OK Load	ASTM D-2783	60 lb.
Four Ball E.P. Test: OK Load	ASTM D-2783	680 kg.
Four Ball Wear Test	ASTM D-2266	.55 mm
Texture	Visual	Tacky
Color	Visual	Off-White